






HIKVISION SPEED DOME KAMERY

	DS-2AF1-401X	DS-2AF1-512 DS-2AF1-502	DS-2AF1-514 DS-2AF1-504	DS-2AF1-516 DS-2AF1-506	DS-2AF1-518 DS-2AF1-508
Model					
Obrazový senzor	1/4" Interline Transfer SONY CCD	1/4" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/4" Sony Super HAD CCD
Efektívne rozlíšenie	PAL: 752 (H)x552 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)
Horizontálne rozlíšenie	500TVL(Color) 570TVL(B/W)	480TVL	480TVL(Color) 520TVL(B/W)	540TVL(Color) 570TVL(B/W)	540TVL(Color) 570TVL(B/W)
Min. osvetlenie	0.7Lux / F1.4 0.02Lux / F1.4 (B/W)	0.1Lux / F1.6	0.2Lux / F1.6 (Color) 0.02Lux / F1.6 (B/W)	0.2Lux/F1.4(Color) 0.02Lux/F1.4(B/W)	0.2Lux/F1.4(Color) 0.02Lux/F1.4(B/W)
Day&Night	ICR	Electronic	ICR	ICR	ICR
Digitálny Zoom	IOx			16x	16x
Zoom	3.8-38mm, IOx	3.9-85.8mm, 22x	3.84-88.4mm, 23x	3.5-105mm, 30x	3.4-122.4mm, 36X
Rozsah PAN	360° endless	360° endless	360° endless	360° endless	360° endless
Rýchlosť otáčania PAN	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 400°/s	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s
Rozsah TILT	-2°~90° (Auto Flip)	-5°~185°(Auto Flip)	-5°~185°(Auto Flip)	-5°~185°(Auto Mirror)	-5°~185°(Auto Mirror)
Rýchlosť otáčania TILT	Tilt Manual Speed: 0.3°~60°/75°/90°/s, Tilt Preset Speed: 200°/s	Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s	Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s	Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s	Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s
Počet presetov	256	256	256	256	256
Sekvencie	8	8	8	8	8
Trasy	4	4	4	4	4
Alarmové vstupy	2 channels	7 channels	7 channels	7 channels	7 channels
Alarmové výstupy	1 channel	2 channels	2 channels	2 channels	2 channels
RS-485 Protokoly	HIKVISION, PELCO-P, PELCO-D, self-adaptive	HIKVISION, PELCO-P, PELCO-D, self-adaptive	HIKVISION, PELCO-P, PELCO-D, self-adaptive	HIKVISION, PELCO-P, PELCO-D, self-adaptive	HIKVISION, PELCO-P, PELCO-D, self-adaptive
Pracovná teplota	-10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) -10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) -10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) -10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) -10°C ~ 50°C (indoor)