











FAREBNÉ ANALÓGOVÉ KAMERY

Model	DS-2CC193P(N)-A	DS-2CC195P(N)-A	DS-2CC197P(N)-A	DS-2CC191P(N)-A	DS-2CC175P(N)-A	DS-2CC176P-A	DS-2CC102P(N)(-A)	DS-2CC112P(N)(-A)	DS-2CC192P(N)(-A)	DS-2CC132P/N	
											
Obrazový senzor	1/3" SONY CCD	1/3" SONY CCD	1/3" SONY vertical double density interline CCD	1/3" SONY Super HAD CCD	1/3" SONY CCD	1/2" SONY EX-View HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/4" CMOS	
Efektívne rozlíšenie	PAL: 752 (H)x582(V) NTSC: 768 (H)x494(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	752(H)x582(V)	PAL: 500(H)x552(V) NTSC: 510(H)x492(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	640(H)x480(V)	
Horizontálne rozlíšenie	540TVL (Color), 600TVL (B/W)	540TVL (Color), 600TVL (B/W)	540TVL (Color), 600TVL (B/W)	540TVL	540TVL (Color), 600TVL (B/W)	540TVL (Color), 600TVL (B/W)	420TVL	480TVL	540TVL	480TVL	
Video norma	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	
Min. osvetlenie	Color: 0.1 Lux @ F1.2, 0.0003Lux @ (F1.2, sensitivity x 256) B&W: 0.01 Lux @ F1.2, 0.00003Lux @ (F1.2, sensitivity x 256)	Color: 0.02Lux @ F1.2, 0.00012Lux @ (F1.2, sensitivity x 256) B&W: 0.002Lux @ F1.2, 0.000007Lux @ (F1.2, sensitivity x 256)	Color: 0.1 Lux @ F1.2, 0.0003Lux @ (F1.2, sensitivity x 256) B&W: 0.01 Lux @ F1.2, 0.00003Lux @ (F1.2, sensitivity x 256)	0.05Lux @ F1.2	Color: 0.1 Lux @ F1.2, 0.0003Lux @ (F1.2, sensitivityx256) B&W: 0.01 Lux @ F1.2, 0.00003Lux @ (F1.2, sensitivityx256)	Color: 0.003Lux @ F1.2, 0.00002Lux @ (F1.2, sensitivityx256) B&W: 0.0003Lux @ F1.2, 0.000002Lux @ (F1.2,sensitivityx256)	0.1 ux @ F1.2	0.1 Lux @ F1.2	0.1 Lux @ F1.2	0.1 Lux @ F1.2	0.1 Lux @ F1.2
Podpor. Typy objektívov	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount DC / Video Drive	C / CS mount	
Day & Night	IR Cut Filter Auto Switch	IR Cut Filter Auto Switch	IR Cut Filter Auto Switch	Electronic	IR Cut Filter Auto Switch	IR Cut Filter Auto Switch	Electronic	Electronic	Electronic	Electronic	
Odstup signál - šum	More than 50dB	More than 50dB	More than 50dB	More than 50dB	More than 50dB	More than 52dB	More than 4SdB	More than 4SdB	More than 4SdB	More than 4SdB	
Rýchlosť elektronickej uzávierky	1/50(1/60)s to 1/100,000s	1/50(1/60)s to 1/100,000s	1/50(1/60)s to 1/100,000s	1/50(1/60)s to 1/100,000s	1/50(1/60)s to 1/100,000s	1/50s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/25 s to 1/15,000 s	
BLC	Area / Intensity / Off	Area / Intensity / Off	Area / Intensity / Off	ON / OFF	Area / Intensity / Off	Area / Intensity / Off	ON / OFF	ON / OFF	ON / OFF	ON / OFF	
WDR	-	-	160X	-	-	-	-	-	-	-	
Synchronizácia	Internal / Power synchronization	Internal / Power synchronization	Internal / Power synchronization	Internal / Power synchronization	Internal / Power synchronization	Internal / Power synchronization	Internal synchronization	Internal synchronization	Internal synchronization	Internal synchronization	
OSD	Yes	Yes	Yes	No	Yes	Yes	No	No	No	No	
Napájanie	24V AC / 20VA ±10%, 12V DC / 300mA ±10%	24V AC / 20VA ±10%, 12V DC / 300mA ±10%	24V AC / 20VA ±10%, 12V DC / 300mA ±10%	24V AC / 12V DC, ±10%	AC 24V±10% / DC 12V±10%	AC 24V±10% / DC 12V±10%	12V DC, ±10%, "- A" series support 12V DC / 24V AC, ±10%.	12V DC, ±10%, "- A" series support 12V DC / 24V AC, ±10%.	12V DC, ±10%, "- A" series support 12V DC / 24V AC, ±10%.	12V DC, ±10%	
Spotreba	5W (10W MAX With ICR Working)	5W (10W MAX With ICR Working)	6.5W (10W MAX With ICR Working)	3W MAX	5W MAX (10W MAX with ICR working)	5W MAX (10W MAX with ICR working)	2W MAX ("-A" series 3.5MAX)	2W MAX ("-A" series 3.5MAX)	2W MAX ("-A" series 3.5MAX)	2W MAX	

Model	DS-2CC511P(N)-A	DS-2CC591P(N)-A	DS-2CC573P-A	DS-2CC575P-A	DS-2CC577P-A	DS-2CC502P(N)-A	DS-2CC512P(N)-A	DS-2CC592P(N)	DS-2CC502P(N)-FB	DS-2CC512P(N)-FB
										
Obrazový senzor	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY CCD	1/3" SONY CCD	1/3" SONY vertical double density interline CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD
Efektívne rozlíšenie	PAL: 752(H)x552(V), NTSC: 768(H)x494(V)	PAL: 752(H)x552(V), NTSC: 768(H)x494(V)	752(H)x552(V)	752(H)x552(V)	752(H)x552(V)	PAL: 500(H)x552(V) NTSC: 510(H)x492(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 500(H)x582(V) NTSC: 510(H)x492(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)
Horizontálne rozlíšenie	4S0TVL	540TVL	540TVL(Color), 600TVL (B/W)	540TVL(Color), 600TVL (B/W)	540TVL(Color), 600TVL (B/W)	420TVL	480TVL	540TVL	420TVL	480TVL
Vídeo norma	PAL/NTSC	PAL/NTSC	PAL	PAL	PAL	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
Min. osvetlenie	0.1 Lux @ F1.2	0.1 Lux @ F1.2	Color: 0.14Lux @ F1.4, 0.0004Lux @ (F1.4, sensitivity x 256) B&W: 0.014Lux @ F1.4, 0.00004Lux @ (F1.4, sensitivity x 256)	Color: 0.027Lux @ F1.4, 0.00016Lux @ (F1.4, sensitivity x 256) B&W: 0.0027Lux @ F1.4, 0.000095Lux @ (F1.4, sensitivity x 256)	Color: 0.14Lux @ F1.4, 0.0004Lux @ (F1.4, sensitivity x 256) B&W: 0.014Lux @ F1.4, 0.00004Lux @ (F1.4, sensitivity x 256)	0.1Lux @ F1.2	0.1Lux @ F1.2	0.1Lux @ F1.2	0.1Lux @ F1.2	0.1Lux @ F1.2
Podpor. Typy objektívov	3.5~9mm Auto Iris Lens (2.8-11mm auto iris lens optional)	3.5~9mm Auto Iris Lens (2.8-11mm auto iris lens optional)	2.8~11mm@F1.4 (2.5~6mm optional)	2.8~11mm@F1.4 (2.5~6mm optional)	2.8~11mm@F1.4 (2.5~6mm optional)	3.6mm @ F2.0 (2.8mm, 6mm, 8mm, 12mm, 16mm optional)	3.6mm @ F2.0 (2.8mm, 6mm, 8mm, 12mm, 16mm optional)	3.6mm @ F2.0 (2.8mm, 6mm, 8mm, 12mm, 16mm optional)	4 ~ 9mm	4 ~ 9mm
Day & Night	Electronic	Electronic	ICR	ICR	ICR	Electronic	Electronic	Electronic	Electronic	Electronic
Odstup signál šum	More than 45dB	More than 45dB	More than 50dB	More than 50dB	More than 50dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB
Rýchlosť elektronickej uzávierky	1/50(1/60)s to 1/100,000s	1/50(1/60)s to 1/100,000s	1/50s to 1/100,000s	1/50s to 1/100,000s	1/50s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s
BLC	ON / OFF	ON / OFF	Area / Intensity / Off	Area / Intensity / Off	Area / Intensity / Off	ON	ON	ON	ON	ON
Synchronizácia	Internal synchronization	Internal synchronization	Internal / Power synchronization	Internal / Power synchronization	Internal / Power synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization
Napájanie	24V AC / 12V DC, ±10%	24V AC / 12V DC, ±10%	24VAC / 20VA ±10%, 12VDC / 300mA ±10%	24VAC / 20VA ±10%, 12VDC / 300mA ±10%	24VAC / 20VA ±10%, 12VDC / 300mA ±10%	12V DC, ±10% (-A) Support 24VAC / 12VDC	12V DC, ±10% (-A) Support 24VAC / 12VDC	12V DC, ±10% (-A) Support 24VAC / 12VDC	12V DC, ±10%	12V DC, ±10%
Spotreba	3.5W MAX	3.5W MAX	4W (10W MAX With ICR Working)	4W (10W MAX With ICR Working)	4W (10W MAX With ICR Working)	2W MAX	2W MAX	2W MAX	2W MAX	2W MAX

Model	DS-2CC592P(N)-FB	DS-2CC532P/N	DS-2CC502P-M	DS-2CC572P-M	DS-2CC502P(N)-IMB	DS-2CC572P(N)-IMB	DS-2CC102P(N)-IRA	DS-2CC112P(N)-IRA	DS-2CC192P(N)-IRA	DS-2CC102P(N)-IR
										
Obrazový senzor	1/3" SONY Super HAD CCD	1/4" CMOS	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD
Efektívne rozlíšenie	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	640(H)x480(V)	500(H)x582(V)	752(H)x582(V)	PAL: 500(H)x582(V) NTSC: 510(H)x492(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 500(H)x582(V) NTSC: 510(H)x492(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 500(H)x582(V) NTSC: 510(H)x492(V)
Horizontálne rozlíšenie	540TVL	480TVL	420TVL	540TVL	420TVL	540TVL	420TVL	480TVL	540TVL	420TVL
Video norma	PAL/NTSC	PAL/NTSC	PAL	PAL	PAL/NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
Min. osvetlenie	0.1 Lux @ F1.2	0.1 Lux @ F1.2	0.1 Lux @ F1.2	0.1 Lux @ F1.2	0.1 Lux @ F1.2(0 Lux with IR)	0.1 Lux @ F1.2(0 Lux with IR)	0.1 Lux @ F1.2 (0 LUX with IR)	0.1 Lux @ F1.2 (0 LUX with IR)	0.1 Lux @ F1.2 (0 LUX with IR)	0.1 Lux @ F1.2 (0 LUX with IR)
Podpor. Typy objektívov	4 ~ 9mm	3.6mm @ F2.0 (2.8mm, 6mm, 8mm, 12mm)	3.6mm @ F2.0	3.6mm @ F2.0	3.6mm(2.8mm, 6mm optional)	3.6mm(2.8mm, 6mm optional)	25mm default (16mm optional)	25mm default (16mm optional)	25mm default (16mm optional)	6mm (3.6mm, 2.8mm optional)
Day & Night	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	-	-	-	-
IR dosvit	-	-	-	-	Approx 10 to 20 meters	Approx 10 to 20 meters	Approx 100 to 110 meters	Approx 100 to 110 meters	Approx 100 to 110 meters	Approx 10 to 20 meters
Odstup signál – šum	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB
Rýchlosť elektronickej uzávierky	1/50 (1/60)s to 1/100,000s	1/25s to 1/15,000s	1/50s to 1/100,000s	1/50s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s
BLC	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON
Synchronizácia	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization
Napájanie	12V DC, ±10%	12V DC, ±10%	DC12V±10%	DC12V±10%	DC12V±10%	DC12V±10%	AC 24V±10% (DC 12V±10% Option)	AC 24V±10% (DC 12V±10% Option)	AC 24V±10% (DC 12V±10% Option)	12V DC, ±10%
Spotreba	2W MAX	2W MAX	2W MAX	2W MAX	3W MAX	3W MAX	15W	15W	15W	3W MAX

Model	DS-2CC112P(N)-IR	DS-2CC192P(N)-IR	DS-2CC102P(N)-IR3	DS-2CC112P(N)-IR3	DS-2CC192P(N)-IR3	DS-2CC102P(N)-IR5	DS-2CC112P(N)-IR5	DS-2CC192P(N)-IR5	DS-2CC102P(N)-IRT	DS-2CC112P(N)-IRT
Obrazový senzor										
Efektívne rozlíšenie	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 500 (H) × 582 (V) NTSC: 510 (H) × 492 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 500 (H) × 582 (V) NTSC: 510 (H) × 492 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 752 (H) × 582 (V) NTSC: 768 (H) × 494 (V)	PAL: 500(H)×582 (V) NTSC: 510(H)×492(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)
Horizontálne rozlíšenie	480TVL	540TVL	420TVL	480TVL	540TVL	420TVL	480TVL	540TVL	420TVL	480TVL
Video norma	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC	PAL / NTSC
Min. osvetlenie	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)
Podpor. Typy objektívov	6mm (3.6mm, 2.8mm optional)	6mm (3.6mm, 2.8mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	16mm (3.6mm, 6mm, 8mm, 12mm optional)	16mm (3.6mm, 6mm, 8mm, 12mm optional)	16mm (3.6mm, 6mm, 8mm, 12mm optional)	4 to 9mm(5-15mm optional), Adjusted by Remote Control	4 to 9mm(5-15mm optional), Adjusted by Remote Control
IR dosvit	Approx 10 to 20 meters	Approx 10 to 20 meters	Approx 30 to 40 meters	Approx 30 to 40 meters	Approx 30 to 40 meters	Approx 50 to 60 meters	Approx 50 to 60 meters	Approx 50 to 60 meters	Approx 30 to 40 meters	Approx 30 to 40 meters
Odstup signál - šum	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB
Rýchlosť elektronickej uzávierky	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (60)s to 1/100,000s	1/50 (60)s to 1/100,000s	1/50 (60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s
BLC	ON	ON	ON	ON	ON	ON	ON	ON	ON	ON
Synchronizácia	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization
Napájanie	12V DC, ±10%	12V DC, ±10%	AC 24V±10% (DC 12V±10% Option)	AC 24V±10% (DC 12V±10% Option)	AC 24V±10% (DC 12V±10% Option)	AC 24V±10% (DC 12V±10% Option)	AC 24V±10% (DC 12V±10% Option)	AC 24V±10% (DC 12V±10% Option)	DC12V/AC24V, ±10%	DC12V/AC24V, ±10%
Spotreba	3W MAX	3W MAX	6W MAX	6W MAX	6W MAX	8W MAX	8W MAX	8W MAX	13W MAX	13W MAX

Model	DS-2CC192P(N)-IRT	DS-2CC502P(N)-IR	DS-2CC512P(N)-IR	DS-2CC592P(N)-IR	DS-2CC502P(N)-IR3	DS-2CC512P(N)-IR3	DS-2CC592P(N)-IR3	DS-2CZ232P(N)	DS-2CZ252P(N)	DS-2CZ282P(N)	DS-2CZ292P(N)
											
Obrazový senzor	1/3" SONY CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/4" SONY Interline Transfer Super HAD CCD	1/4" SONY Interline Transfer Super HAD CCD	1/4" SONY Interline Transfer Super HAD CCD	1/4" SONY Interline Transfer Super HAD CCD
Efektívne rozlíšenie	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	752(H)×582(V)	752(H)×582(V)	752(H)×582(V)	752(H)×582(V)
Horizontálne rozlíšenie	540TVL	420TVL	480TVL	540TVL	420TVL	480TVL	540TVL	540 TVL	Color: 540 TVL; B/ W: 600 TVL	540 TVL (Color) 600 TVL (B/W)	540 TVL (Color) 600 TVL (B/W)
Video norma	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC	PAL/NTSC
Min. osvetlenie	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.1Lux @ F1.2 (0 LUX with IR)	0.2Lux @ F1.6	Color: 0.2Lux @ F1.6; B/W: 0.02Lux @ F1.6	Color: 0.2Lux @ F1.4, 0.008Lux @ F1.4 (sensitivity×256) B/W: 0.02Lux @ F1.4, 0.008Lux @ F1.4 (sensitivity×256)	Color: 0.2Lux @ F1.4, 0.008Lux @ F1.4 (sensitivity×256) B/W: 0.02Lux @ F1.4, 0.008Lux @ F1.4 (sensitivity×256)
Podpor. Typy objektívov	4 to 9mm(5-15mm optional), Adjusted by	6mm (3.6mm, 2.8mm optional)	6mm (3.6mm, 2.8mm optional)	6mm (3.6mm, 2.8mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	22X Optical Zoom F1.6, f=3.9 ~ 85.8mm	23X Optical Zoom F1.6, f=3.84 ~ 88.4mm	30X Optical Zoom F1.4, f=3.5 ~ 105mm	36X Optical Zoom F1.4, f=3.4 ~ 122.4mm
Day & Night	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	IR Cut Filter Auto Switch	IR Cut Filter Auto Switch	IR Cut Filter Auto Switch
Odstup signál – šum	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 48 dB	More than 52dB	More than 52dB	More than 52dB	More than 52dB
Rýchlosť elektronickej uzávierky	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50 (1/60)s to 1/100,000s	1/50s to 1/100,000s	1/50s to 1/100,000s	1/50s to 1/100,000s	1/50s to 1/100,000s
BLC	ON	ON	ON	ON	ON	ON	ON	Area / Intensity / Off	Area / Intensity / Off	Area / Intensity / Off	Area / Intensity / Off
Synchronizácia	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization	Internal Synchronization
OSD	No	No	No	No	No	No	No	Yes	Yes	Yes	Yes
IR dosvit	Approx 30 to 40 meters	Approx 10 to 20 meters	Approx 10 to 20 meters	Approx 10 to 20 meters	Approx 30 to 40 meters	Approx 30 to 40 meters	Approx 30 to 40 meters	-	-	-	-
Napájanie	12V DC/AC 24V, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%	12V DC, ±10%
Spotreba	13W MAX	3W MAX	3W MAX	3W MAX	6W MAX	6W MAX	6W MAX	4W MAX	4.5W MAX	4.5W MAX	4.5W MAX