

## SIETOVÉ SPEED DOME KAMERY

	DS-2DF1-401H	DS-2DF1-512 DS-2DF1-502	DS-2DF1-514 DS-2DF1-504	DS-2DF1-516 DS-2DF1-506	DS-2DF1-518 DS-2DF1-508	DS-2DF1-672
<b>Model</b>						
<b>Obrazový senzor</b>	1/4" Interline Transfer SONY CCD	1/4" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/4" Sony Super HAD CCD	1/3" Sony Progressive Scan CCD
<b>Efektívne rozlíšenie</b>	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	1280(H)x960(V)
<b>Horizontálne rozlíšenie</b>	500TVL(Color) 570TVL(B/W)	480TVL	480TVL(Color) 520TVL(B/W)	540TVL(Color) 570TVL(B/W)	540TVL(Color) 570TVL(B/W)	
<b>Min. osvetlenie</b>	0.7Lux / F1.4 (Color) 0.02Lux / F1.4 (B/W)	0.1Lux / F1.6	0.2Lux / F1.6 (Color) 0.02Lux / F1.6 (B/W)	0.2Lux/F1.4(Color) 0.02Lux/F1.4(B/W)	0.2Lux/F1.4(Color) 0.02Lux/F1.4(B/W)	0.1Lux/F1.6(Color) 0.01Lux/F1.6(B/W)
<b>Day&amp;Night</b>	ICR	Electronic	ICR	ICR	ICR	ICR
<b>Digitálny Zoom</b>	10x	-	-	16x	16x	12x
<b>Zoom</b>	3.8-38mm, 10x	3.9-85.8mm, 22x	3.84-88.4mm, 23x	3.5-105mm, 30x	3.4-122.4mm, 36X	4.7-84.6mm, 18x
<b>Rozsah PAN</b>	360° endless	360° endless	360° endless	360° endless	360° endless	360° endless
<b>Rýchlosť otáčania PAN</b>	Pan Manual Speed: 0.1°~300°/220°/300°/s, Pan Preset Speed: 400°/s	Pan Manual Speed Pan Preset Speed: 0.1°~300°/s, 540°/s	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s	Pan Manual Speed: 0.1° ~300°/s, Pan Preset Speed: 540°/s	Pan Manual Speed: 0.1° ~300°/s, Pan Preset Speed: 540°/s	Pan Manual Speed: 0.1°~75°/s, Pan Preset Speed: 75°/s
<b>Rozsah TILT</b>	-2°~90° (Auto Flip)	-5°~185°(Auto Flip)	-5°~185°(Auto Flip)	-5°~185°(Auto Mirror)	-5°~185°(Auto Mirror)	-5°~90°
<b>Rýchlosť otáčania TILT</b>	Tilt Manual Speed: 0.1°~90°/s Tilt Preset Speed: 200°/s	Tilt Manual Speed 0.1°~240°/s, Tilt Preset Speed: 400°/s	Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s	Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s	Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s	Tilt Manual Speed: 0.1°~50°/s, Tilt Preset Speed: 50°/s
<b>Počet presetov</b>	256	256	256	256	256	256
<b>Sekvencie</b>	8	8	8	8	8	8
<b>Trasy</b>	4	4	4	4	4	4
<b>Video kompresia</b>	H.264	H.264	H.264	H.264	H.264	H.264
<b>Max. rozlíšenie obrazu</b>	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480	1280x960
<b>Počet snímkov za sekundu</b>	25fps (704x576) 30fps (704x480)	25fps (704x576) 30fps (704x480)	25fps (704x576) 30fps (704x480)	25fps (704x576) 30fps (704x480)	25fps (704x576) 30fps (704x480)	12.5fps (1280x960), 25 fps (1280x720), 25 fps (640x480)
<b>Viacúrovňové</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Alarmové vstupy</b>	1 channel	7 channels	7 channels	7 channels	7 channels	1 channel
<b>Alarmové výstupy</b>	1 channel	2 channels	2 channels	2 channels	2 channels	1 channel
<b>Pracovná teplota</b>	-10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) -10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) -10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) - 10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) - 10°C ~ 50°C (indoor)	-30°C ~ 65°C (outdoor) - 10°C ~ 50°C (indoor)