



































HIKVISION IP KAMERY

	DS-2CDSS6BF(MF)-E	DS-2CD883F-E(W)	DS-2CD876BF	DS-2CD863PF(NF)-E(W)	DS-2CD854F-E(W)	DS-2CD853F-E(W)	DS-2CD893PFWD(NFWD)-E(W)	DS-2CD893PF(NF)-E(W)	
Model									
Obrazový senzor	1/2.5" Progressive Scan CMOS	1/2.5" Progressive Scan CMOS	1/1.8" SONY Progressive Scan CCD	1/3" SONY Progressive Scan CCD	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" SONY vertical double density interline CCD	1/3" SONY CCD	
Min. osvetlenie	Color: 0.6 Lux @ F1.2 B/W: 0.08 Lux @ F1.2	Color: 0.6Lux @ F1.2 B/W: 0.08Lux @ F1.2	Color: 0.5 Lux @ F1.2; B/W: 0.05 Lux @ F1.2	Color: 0.1Lux @ F1.2 B/W: 0.01Lux @ F1.2	Color: 0.6Lux @ F1.2 B/W: 0.08Lux @ F1.2	Color: 0.5Lux @ F1.2, 0.1Lux @ (F1.2, sensitivityxS) B/W: 0.05Lux @ F1.2, 0.01Lux @ (F1.2, sensitivityxS)	Color: 0.1Lux @ F1.2 B/W: 0.01Lux @ F1.2	Color: 0.02Lux @ F1.2 B / W: 0.002Lux @ F1.2	
Podpor. typy objektívov	C/CS mount	C/CS mount DC	C/CS mount	C/CS mount DC	C/CS mount DC	C/CS mount DC	C/CS mount DC	C/CS mount DC	
Day & Night	ICR	ICR	ICR	ICR	ICR	ICR	ICR	ICR	
Video kompresia	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	
Max. rozlíšenie	2560x1920	2560x1920	1600x1200	1280 x 960	2048 x 1536	1600 x 1200	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480	
FPS	50Hz	8fps(2560x1920) 20fps(2048x1536) 25fps(FULL HD1080P) 25fps(HD720P)	6fps(2560x1920) 12.5fps(2048x1536) 25fps(1920x1080) 25fps(1600x1200) 25fps(1280x720)	25fps(1200x1600)	12.5fps(1280x960) 25fps(1280 x 720)	12.5fps (2045x1536) 25fps (1920x1080) 25fps (1600x1200)	12.5fps (1600x1200) 12.5fps (1600x912) 25fps (1280x960) 25fps (1280x720)	25fps (704x576)	25fps (704x576)
	60Hz	8fps(2560x1920) 20fps(2048x1536) 30fps(1920x1080) 30fps(1280x720)	7.5fps(2560x1920) 15fps(2048x1536) 30fps(1920x1080) 30fps(1600x1200) 30fps(1280x720)	25fps(1200x1600)	15fps(1280x960) 30fps(1280 x 720)	15fps (2045x1536) 30fps (1920x1080) 30fps (1600x1200)	15fps (1600x1200) 15fps (1600x912) 25fps (1280x960) 30fps (1280x720)	30fps (704x480)	30fps (704x480)
Ochrana heslom	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Power over Ethernet (PoE)	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes	
Pohybová detekcia	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Dual Stream	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Záznam na SD kartu	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Audio vstup / výstup	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	
Alarmový vstup / výstup	4/3	1/1	4/3	1/1	1/1	1/1	1/1	1/1	

	DS-2CD833F-E(W)	DS-2CD8153F-E(W)(I)	DS-2CD8133F-E(W)(I)	DS-2CD892PF (NF) (-E) (-W)	DS-2CD812PF (NF) (-E) (-W)	DS-2CD802PF (NF) (-E) (-W)	
Model							
Obrazový senzor	1/4" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	
Efektívne rozlíšenie				PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)	
Min. osvetlenie	Color: 0.2Lux @ F1.2 B/W: 0.02Lux @ F1.2	0.5Lux @ F1.2 0.1Lux @ (F1.2, sense 1.1Lux @ F1.8, 0.2Lux @ (F1.8, sense up×5) up×5)	0.4 Lux @ F1.2 0.9 Lux @ F1.8	0.1Lux @ F1.2	0.1Lux @ F1.2	0.1Lux @ F1.2	
Horizontálne rozlíšenie				540TVL	480TVL	420TVL	
Podpor. Typy objektívov	C/CS mount DC	4mm@F1.8 Angle of view: 54.9°	4mm@F1.8, Angle of view: 54.9°	C/CS mount DC/Video	C/CS mount DC/Video	C/CS mount DC/Video	
Day & Night	ICR	Electronic	Electronic	Electronic	Electronic	Electronic	
Video kompresia	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	
Max. rozlíšenie	640×480	1600×1200	640×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	
FPS	50Hz	25fps (640×480)	12.5fps (1600×1200) 12.5fps (1600×912) 25fps (1280×960) 25fps (1280×720)	25fps(640×480)	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)
	60Hz	30fps (640×480)	15fps (1600×1200) 15fps (1600×912) 25fps (1280×960) 30fps (1280×720)	30fps(640×480)	30fps (704×480)	30fps (704×480)	30fps (704×480)
Ochrana heslom	Yes	Yes	Yes	Yes	Yes	Yes	
Power over Ethernet (PoE)	Yes	Yes	Yes	Yes	Yes	Yes	
Pohybová detekcia	Yes	Yes	Yes	Yes	Yes	Yes	
Dual Stream	Yes	Yes	Yes	Yes	Yes	Yes	
Záznam na SD kartu	Yes	Yes	Yes	Yes	Yes	Yes	
Audio vstupy / výstupy	1/1	Built-in Microphone and Speaker	Built-in Microphone and Speaker	1/1	1/1	1/1	
Alarmové vstupy / výstupy	1/1	-	-	1/1	1/1	1/1	

Model	DS-2CD892P(N)-IR5	DS-2CD812P(N)-IR5	DS-2CD802P(N)-IR5	DS-2CD892P(N)-IR3	DS-2CD812P(N)-IR3	DS-2CD802P(N)-IR3	DS-2CD892P(N)-IR1	DS-2CD812P(N)-IR1	DS-2CD802P(N)-IR1	
										
Obrazový senzor	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	
Efektívne rozlíšenie	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 752(H)×582(V) NTSC: 768(H)×494(V)	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)	
Min. osvetlenie	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	0.1Lux @ F1.2 (0 Lux With IR)	
Horizontálne rozlíšenie	540TVL	480TVL	420TVL	540TVL	480TVL	420TVL	540TVL	480TVL	420TVL	
Podporované typy objektívov	16mm (3.6mm, 6mm, 8mm, 12mm optional)	16mm (3.6mm, 6mm, 8mm, 12mm optional)	16mm (3.6mm, 6mm, 8mm, 12mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	12mm (3.6mm, 6mm, 8mm, 16mm optional)	6mm (2.8mm, 3.6mm optional)	6mm (2.8mm, 3.6mm optional)	6mm (2.8mm, 3.6mm optional)	
Day & Night	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	
Video kompresia	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	
Max. rozlíšenie	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	PAL: 704×576 NTSC: 704×480	
FPS	50Hz	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)	25 fps (704×576)
	60Hz	30fps (704×480)	30fps (704 × 480)	30fps (704×480)	30fps (704×480)	30fps (704×480)	30fps (704×480)	30fps (704×480)	30fps (704×480)	30fps (704×480)
Ochrana heslom	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Power over Ethernet (PoE)	No	No	No	No	No	No	No	No	No	
Pohybová detekcia	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Dual Stream	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
Záznam na SD kartu	No	No	No	No	No	No	No	No	No	
Audio vstupy / výstupy	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	
Alarmové vstupy / ýstupy	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1	
IR dosviť	Approx 50 to 60 meters	Approx 50 to 60 meters	Approx 50 to 60 meters	Approx 30 to 40 meters	Approx 30 to 40 meters	Approx 30 to 40 meters	Approx 10 to 20 meters	Approx 10 to 20 meters	Approx 10 to 20 meters	

Model	DS-2CD763PF(NF)-E(I)	DS-2CD754F-E(I)	DS-2CD753F-E(I)	DS-2CD793PF(NF)WD-E(I)	DS-2CD793PF(NF)-E(I)	DS-2CD733F-E(I)	
							
Obrazový senzor	1/3 " SONY progressive scan CCD	1/3" Progressive Scan CMOS	1/3" Progressive Scan CMOS	1/3" SONY vertical double density interline CCD	1/3 " SONY CCD	1/4" Progressive Scan CMOS	
Min. osvetlenie	0.1 Lux @ F1.2 -I: 0 Lux with IR on	0.6Lux @ F1.2 I.Lux @ F1.6 -I: 0 Lux with IR on	0.5Lux @ F1.2, 0.1Lux sensitivity x5 -I: 0 Lux with IR on @ (F1.2,	0.14Lux @ F1.4 -I: 0 Lux with IR on	0.027Lux @ F1.4 -I: 0 Lux with IR on	0.27 Lux @ F1.4 -I: 0 Lux with IR on	
Podporované typy objektívov	2.7-9mm @ F1.2 Angle of view: 101°~30.4° DC	4.5-10mm @ F1.6 Angle of view: 71.5°~33.5° DC	2.7-9mm @ F1.2 Angle of view: 101°~30.4° DC	2.8-11mm @ F1.4 Angle of view: 97°~24° DC	2.8-11mm @ F1.4 Angle of view: 97°~24° DC	2.8-11mm @ F1.4 Angle of view: 70°~18° DC	
Day & Night	Electronic (-I:ICR)	Electronic (-I:ICR)	Electronic (-I:ICR)	Electronic (-I:ICR)	Electronic (-I:ICR)	Electronic (-I:ICR)	
Video kompresia	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	H.264/MJPEG	
Max. rozlíšenie	1280 x 960	2045x1536	1600 x 1200	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480	640x480	
FPS	50Hz	12.5fps (1280x960) 25fps (1280x720)	12.5fps (2045x1536) 25fps (1920x1080) 25fps (1600x1200)	12.5fps (1600x1200) 25fps (1280x720)	25fps (704x576)	25fps (704x576)	25fps (640x480)
	60Hz	15fps (1280x960) 30fps (1280x720)	15fps (2045x1536) 30fps (1920x1080) 30fps (1600x1200)	15fps (1600x1200) 30fps (1280x720)	30fps (704x480)	30fps (704x480)	30fps (640x480)
Ochrana heslom	Yes	Yes	Yes	Yes	Yes	Yes	
Power over Ethernet (PoE)	Yes	Yes	Yes	Yes	Yes	Yes	
Pohybová detekcia	Yes	Yes	Yes	Yes	Yes	Yes	
Dual Stream	Yes	Yes	Yes	Yes	Yes	Yes	
Záznam na SD kartu	Yes	Yes	Yes	Yes	Yes	Yes	
Audio vstupy / výstupy	1/1	1/1	1/1	1/1	1/1	1/1	
Alarm vstupy / výstupy	2/2	1/1	2/2	2/2	2/2	2/2	

Model	DS-2CD7153-E	DS-2CD7133-E	DS-2CD762MF-(I)FB(H)	DS-2CD752MF-(I)FB(H)	DS-2CD792PF(NF) -E	DS-2CD712PF(NF)-E	DS-2CD702PF(NF)-E
							
Obrazový senzor	1/3" CMOS	1/4" CMOS	1/3" SONY progressive scan CCD	1/3" CMOS	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD
Efektívne rozlíšenie	-	-	-	-	PAL: 752 (H)x582 (V) NTSC: 768 (H)x494 (V)	PAL: 752(H)x582(V) NTSC: 768(H)x494(V)	PAL: 500(H)x582(V) NTSC: 500(H)x582(V)
Min. osvetlenie	0.5 Lux @ F1.2	0.4 Lux @ F1.2	O.ILux @ F1.2	0.5Lux @ F1.2; O.ILux @ F1.2, sense up x 5	O.ILux @ F1.2	O.ILux @ F1.2	O.ILux @ F1.2
Horizontálne rozlíšenie	-	-	-	-	540TVL	480TVL	420TVL
Podporované typy objektívov	4mm, F1.8 Fixed Iris(2.8, 6, 8mm optional)	4mm, F1.8 Fixed Iris(2.8, 6, 8mm optional)	2.7~9mm @ F1.4 /Auto Iris lens	2.7~9mm@ F1.2 / Fixed Iris lens	3.5~9mm @ F1.2 / 014 / Fixed Iris lens	3.5~9mm @ F1.2 / 014 / Fixed Iris lens	3.5~9mm @ F1.2 / 014 / Fixed Iris lens
Day & Night	Electronic	Electronic	ICR	Electronic (ICR Option)	Electronic	Electronic	Electronic
Video kompresia	H.264/MJPEG	H.264/MJPEG	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4	H.264 or MPEG-4
Max. rozlíšenie	1600x1200	640x480	1280x960	1600x1200	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480	PAL: 704x576 NTSC: 704x480
FPS	50Hz	12.5fps (1600x1200) 12.5fps (1600 x 912) 25fps (1280x960) 25fps (1280x720)	12.5fps(1280x960) 25fps(1280x720)	12.5fps(1600x1200) 25fps(1280x720) 25fps(704x576)	25 fps (704x576)	25 fps (704x576)	25 fps (704x576)
	60Hz	15fps (1600x1200) 15fps (1600 x 912) 25fps (1280x960) 30fps (1280x720)	15fps(1280x960) 24fps(1280x720)	10fps(1600x1200) 15fps(1280x720) 30fps(704x576)	30fps (704x480)	30fps (704x480)	30fps (704x480)
Ochrana heslom	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Power over Ethernet (PoE)	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Pohybová detekcia	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Dual Stream	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Záznam na SD kartu	No	No	Yes	Yes	Yes	Yes	Yes
Audio vstup / výstup	-	-	1/1	1/1	1/1	1/1	1/1
Alarm vstup / výstup	-	-	1/1	1/1	1/1	1/1	1/1